

# EL 355 E4 01


112369

- Innovative, high-efficiency diagonal fan
- Optimally tuned, CFD-optimized aerodynamics
- The benchmark for efficiency since 2007
- Robust single phase AC motor
- Conveyed medium temperature up to 80 °C in continuous operation
- Housing made of galvanized steel sheet



## FAN CURVES

Name	Value	Unit
Volume flow	0	m³/h
Pressure	0	Pa



to the product detail page

## GENERAL DATA

Name	Value	Unit	Formula symbol
Labeling	CE, UKCA		
Duct size	-		WxHduct
Pipe connection size (DN)	DN355		DN
Rated voltage (entire device)	230	V	U <sub>rated</sub>
Phases (entire device)	1~		phase
Electrical protection (entire device)	6 A		fuse
Housing material	Galvanized steel		matcasing
Impeller material	Plastic		matimpeller
IP-protection class (entire device)	IPX4		IP <sub>compl</sub>
IP-Protection class (terminal box)	IP44		IP <sub>ebox</sub>
Weight	13.65	kg	m
Fan type	Diagonal		Fa <sub>ntype</sub>
Category / Installation situation	A		cat

## MAXIMAL DATA

Name	Value	Unit	Formula symbol
Max. power consumption (device)	150	W	P <sub>ed, max</sub>
Max. operating current (device)	0.98	A	I <sub>ed, max</sub>
Max. speed	1460	1/min	n <sub>max</sub>
Max. stat. efficiency	46.3	%	η <sub>es</sub>
Max. fan efficiency	50.5	%	η <sub>e</sub>
Max. flowrate	2580	m <sup>3</sup> /h	Q <sub>v, max</sub>
Max. stat pressure	270	Pa	p <sub>sf, max</sub>
Max. medium temperature	80	°C	T <sub>m, max</sub>
Max. environment temperature	80	°C	T <sub>amb, max</sub>
Min. environment temperature	-25	°C	T <sub>amb, min</sub>
Min. voltage	80	V	U <sub>min</sub>
Stall current	1.99	A	I <sub>LRA</sub>



to the product detail page

## MOTOR DATA

Name	Value		Unit	Formula symbol
	50 Hz	60 Hz		
Rated frequency (device)		50		f
Motor type		AC 1~		phase
Control type		stepless-controlled		ctrltype
Installation type		IRM (In)		install
Rotation direction		right		rotation
Isolation class		ISO F		ISOclass
Motor-protection		TMI		protectmotor
Protection class		IP00		IPmotor
Is pole-changeable		No		polexch
Type of power supply		AC 1~		pwrsupmotor
Capacity capacitor		4	µF	Ccond
Voltage capacitor		450	V	VUcond
Number of poles (1)		4.000000		num polesw1
Rated voltage	230		V	Urated, f1
Rated current	0.7		A	Irated, f1
Shaft power	100		W	Pout, f1
Speed	1430		1/min	n1
UL-Certification motor		None		ULcert

## ERP DATA (LOT11)

Name	Value	Unit	Formula symbol
Speed at the energy efficiency optimum	1438	1/min	n <sub>opt</sub>
Efficiency level	46.8	%	N
Efficiency category	statisch		catefficiency
Input power of the motor at the energy efficiency optimum	0.15	kW	P <sub>e, opt</sub>
Overall efficiency	66	%	η <sub>ges</sub>
Measurement category	A		meas cat
Fan pressure at energy efficiency optimum	155	Pa	p <sub>f, opt</sub>
Flowrate at energy efficiency optimum	1692	m³/h	Q <sub>v, opt</sub>



to the product detail page