

# KVR 8050 EC 30


131370

- Backward curved centrifugal impeller
- Removable fan unit
- Housing made of galvanized sheet steel
- High efficiency EC motor, steplessly controllable
- Conveyed medium temperature up to 50 °C in continuous operation



## FAN CURVES

Name	Value	Unit
Volume flow	0	m³/h
Pressure	0	Pa



to the product detail page

# KVR 8050 EC 30

131370

**ruck**

## GENERAL DATA

Name	Value	Unit	Formula symbol
Labeling	CE, UKCA		
Duct size	800x500		WxHduct
Pipe connection size (DN)	-		DN
Rated voltage (entire device)	400	V	U <sub>rated</sub>
Phases (entire device)	3~		phase
Electrical protection (entire device)	6 A		fuse
Housing material	Galvanized steel		matcasing
Impeller material	Plastic		matimpeller
IP-protection class (entire device)	IPX4		IP <sub>compl</sub>
IP-Protection class (terminal box)	IP44		IP <sub>ebox</sub>
Weight	58.05	kg	m
Nominal air flow rate, nominal point m <sup>3</sup> /h	4302	m <sup>3</sup> /h	q <sub>Vnom</sub>
Nominal external pressure, static	494	Pa	p <sub>s,nom</sub>
Fan type	Radial		Fan <sub>type</sub>
Category / Installation situation	A		cat

## ERP DATA (LOT 6)

Name	Value	Unit	Formula symbol
Nominal air flow rate, nominal point m <sup>3</sup> /s	1.2	m <sup>3</sup> /s	q <sub>V,nom</sub>
Actual electrical input power, nominal point	0.88	kW	P <sub>e,nom</sub>
Face velocity, nominal point	3	m/s	V <sub>nom</sub>
Nominal external pressure, static	494	Pa	p <sub>s,nom</sub>
supply air fan static efficiency, nominal point	65.6	%	η <sub>es,SUP</sub>
Highest external air leakage rate	0.04	%	
Enclosure sound level, nominal point	76	dB(A)	L <sub>WA2</sub>
Rating	Product is compliant 2018		



to the product detail page

# KVR 8050 EC 30

131370

**ruck**

## MAXIMAL DATA

Name	Value		Unit	Formula symbol
	50 Hz	60 Hz		
Max. power consumption (device)	1328	1328	W	P <sub>ed, max</sub>
Max. operating current (device)	2.05	2.05	A	I <sub>ed, max</sub>
Max. speed	1600	1600	1/min	n <sub>max</sub>
Max. stat. efficiency	62.5	62.5	%	η <sub>es</sub>
Max. fan efficiency	63.2	63.2	%	η <sub>e</sub>
Max. flowrate	9550	9550	m <sup>3</sup> /h	q <sub>v, max</sub>
Max. stat pressure	1160	1160	Pa	p <sub>sf, max</sub>
Max. medium temperature	50	50	°C	T <sub>m, max</sub>
Max. environment temperature	50	50	°C	T <sub>amb, max</sub>
Min. environment temperature	-25	-25	°C	T <sub>amb, min</sub>

## MOTOR DATA

Name	Value		Unit	Formula symbol
	50 Hz	60 Hz		
Rated frequency (device)		50		f
Motor type		EC		phase
Control type		stepless-controlled		ctrltype
Installation type		ORM (Out)		install
Rotation direction		right		rotation
Isolation class		ISO F		ISOclass
Motor-protection		TEC		protectmotor
Protection class		IP55		IP <sub>motor</sub>
Is pole-changeable		No		polexch
Type of power supply		AC 3~		pwsup <sub>motor</sub>
Rated voltage	400		V	U <sub>rated, f1</sub>
Rated current	2.1		A	I <sub>rated, f1</sub>
Shaft power	1320		W	P <sub>out, f1</sub>
Speed	1350		1/min	n <sub>f1</sub>
Min. temperature	-25		°C	T <sub>motor, min</sub>
UL-Certification motor		UL recognized		ULcert



to the product detail page