

RS 315 EC K 01


159763

- Compact centrifugal fan
- Backward curved impeller
- Sheet steel housing, RAL 7035, powder coated
- High efficiency EC motor, steplessly controllable
- Conveyed medium temperature up to 50 °C in continuous operation
- Internal electronic temperature monitoring



FAN CURVES

Name	Value	Unit
Volume flow	0	m³/h
Pressure	0	Pa



to the product detail page

GENERAL DATA

Name	Value	Unit	Formula symbol
Labeling	CE, UKCA		
Duct size	-		WxHduct
Pipe connection size (DN)	DN315		DN
Rated voltage (entire device)	230	V	U _{rated}
Phases (entire device)	1~		phase
Electrical protection (entire device)	6 A		fuse
Housing material	Steel		matcasing
Impeller material	Plastic		matimpeller
IP-protection class (casing)	IPX4		IP _{casing}
IP-protection class (entire device)	IPX4		IP _{compl}
IP-Protection class (terminal box)	IP44		IP _{ebox}
Weight	4.9	kg	m
Nominal air flow rate, nominal point m ³ /h	1116	m ³ /h	q _{v,nom}
Nominal external pressure, static	154	Pa	p _{s,nom}
Fan type	Radial		F _{antype}
Category / Installation situation	B		cat

ERP DATA (LOT 6)

Name	Value	Unit	Formula symbol
Nominal air flow rate, nominal point m ³ /s	0.31	m ³ /s	q _{v,nom}
Actual electrical input power, nominal point	0.16	kW	P _{e,nom}
Face velocity, nominal point	3.97	m/s	v _{nom}
Nominal external pressure, static	154	Pa	p _{s,nom}
static efficiency of the extract fan, nominal point	30.51	%	η _{es,EHA}
Highest external air leakage rate	1.4	%	
Enclosure sound level, nominal point	60.83	dba	LWA2
Rating	Product is compliant 2018		



to the product detail page

MAXIMAL DATA

Name	Value		Unit	Formula symbol
	50 Hz	60 Hz		
Max. power consumption (device)	160	160	W	$P_{ed, max}$
Max. operating current (device)	1.3	1.3	A	$I_{ed, max}$
Max. speed	2800	2800	1/min	n_{max}
Max. stat. efficiency	42.8	42.8	%	η_{es}
Max. fan efficiency	43.4	43.4	%	η_e
Max. flowrate	1340	1340	m ³ /h	$Q_{v, max}$
Max. stat pressure	620	620	Pa	$p_{sf, max}$
Max. medium temperature	50	50	°C	$T_{m, max}$
Max. environment temperature	50	50	°C	$T_{amb, max}$
Min. environment temperature	-30	-30	°C	$T_{amb, min}$

MOTOR DATA

Name	Value		Unit	Formula symbol
	50 Hz	60 Hz		
Rated frequency (device)		50		f
Motor type		EC		phase
Control type		stepless-controlled		ctrltype
Installation type		ORM (Out)		install
Rotation direction		right		rotation
Isolation class		ISO F		ISOclass
Motor-protection		TEC		protectmotor
Protection class		IP54		IPmotor
Is pole-changeable		No		polexch
Type of power supply		AC 1~		pwrsupmotor
Rated voltage	230		V	$U_{rated, f1}$
Rated current	1.2		A	$I_{rated, f1}$
Shaft power	165		W	$P_{out, f1}$
Speed	2600		1/min	n_{f1}
Efficiency	46.9		%	$\eta_{m, f1}$
Min. temperature	-30		°C	$T_{motor, min}$
Cos Phi	0.600000	0.000000		$\cos \varphi$
UL-Certification motor		None		ULcert



to the product detail page