

RS 315L EC


131515

- Compact centrifugal fan
- Backward curved impeller
- Sheet steel housing, RAL 7035, powder coated
- High efficiency EC motor, steplessly controllable
- Conveyed medium temperature up to 65 °C in continuous operation
- Internal electronic temperature monitoring



FAN CURVES

Name	Value	Unit
Volume flow	0	m³/h
Pressure	0	Pa



to the product detail page

GENERAL DATA

Name	Value	Unit	Formula symbol
Labeling	CE, UKCA		
Duct size	-		WxHduct
Pipe connection size (DN)	DN315		DN
Rated voltage (entire device)	230	V	U _{rated}
Phases (entire device)	1~		phase
Electrical protection (entire device)	6 A		fuse
Housing material	Steel		matcasing
Impeller material	Galvanized steel		matimpeller
IP-protection class (casing)	IPX4		IP _{casing}
IP-protection class (entire device)	IPX3		IP _{compl}
IP-Protection class (terminal box)	IP44		IP _{ebox}
Weight	6	kg	m
Nominal air flow rate, nominal point m ³ /h	856.8	m ³ /h	q _{v,nom}
Nominal external pressure, static	320	Pa	p _{s,nom}
Fan type	Radial		Fantype
Category / Installation situation	A		cat

ERP DATA (LOT 6)

Name	Value	Unit	Formula symbol
Nominal air flow rate, nominal point m ³ /s	0.24	m ³ /s	q _{v,nom}
Actual electrical input power, nominal point	0.15	kW	P _{e,nom}
Face velocity, nominal point	3.1	m/s	v _{nom}
Nominal external pressure, static	320	Pa	p _{s,nom}
supply air fan static efficiency, nominal point	61	%	η _{es,SUP}
Highest external air leakage rate	1.83	%	
Enclosure sound level, nominal point	80	dba	L _{WA2}
Rating	Product is compliant 2018		



to the product detail page

MAXIMAL DATA

Name	Value		Unit	Formula symbol
	50 Hz	60 Hz		
Max. power consumption (device)	270	270	W	$P_{ed, max}$
Max. operating current (device)	1.89	1.89	A	$I_{ed, max}$
Max. speed	2950	2950	1/min	n_{max}
Max. stat. efficiency	47.5	47.5	%	η_{es}
Max. fan efficiency	48.2	48.2	%	η_e
Max. flowrate	1990	1990	m ³ /h	$Q_{v, max}$
Max. stat pressure	760	760	Pa	$p_{sf, max}$
Max. medium temperature	65	65	°C	$T_{m, max}$
Max. environment temperature	65	65	°C	$T_{amb, max}$
Min. environment temperature	-30	-30	°C	$T_{amb, min}$

MOTOR DATA

Name	Value		Unit	Formula symbol
	50 Hz	60 Hz		
Rated frequency (device)		50		f
Motor type		EC		phase
Control type		stepless-controlled		ctrltype
Installation type		ORM (Out)		install
Rotation direction		right		rotation
Isolation class		ISO F		ISOclass
Motor-protection		TEC		protectmotor
Protection class		IP30		IP _{motor}
Is pole-changeable		No		polexch
Type of power supply		AC 1~		pwrsupmotor
Rated voltage	230	230	V	$U_{rated, f1}$
Rated current	1.74	1.74	A	$I_{rated, f1}$
Shaft power	272	272	W	$P_{out, f1}$
Speed	2547	2547	1/min	n_{f1}
Efficiency	52		%	$\eta_{m, f1}$
Min. temperature		-30	°C	$T_{motor, min}$
Cos Phi	0.000000	0.680000		$\cos \varphi$
UL-Certification motor		None		ULcert



to the product detail page